

Safety data sheet

Page: 1/16

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 14.10.2021 Version: 4.0

Product: N85-021 Thinner 1L

(ID no. 50775814/SDS_GEN_00/EN)

Date of print 09.03.2022

1. Identification

Product identifier

N85-021 Thinner 1L

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Thinner

Details of the supplier of the safety data sheet

Company:

BASF France SAS 49, avenue Georges Pompidou 92593 Levallois-Perret Cedex, FRANCE

Telephone: +33 1 4964-5732

E-mail address: securite-produits.france@basf.com

Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

2. Hazards Identification

Classification of the substance or mixture

According to UN GHS criteria

Skin Corr./Irrit. 2 Eye Dam./Irrit. 2A Asp. Tox. 1 STOT SE 3 (Vapours may cause drowsiness and dizziness.) Aquatic Acute 3

Date / Revised: 14.10.2021 Version: 4.0

Product: N85-021 Thinner 1L

(ID no. 50775814/SDS_GEN_00/EN)

Date of print 09.03.2022

Aquatic Chronic 3 Flam. Liq. 3

For the classifications not written out in full in this section the full text can be found in section 16.

Label elements

Globally Harmonized System, UN (GHS)

Pictogram:







Signal Word:

Danger

Hazard Statement:

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, protective clothing and eye protection or face

protection.

P264 Wash contaminated body parts thoroughly after handling.

P242 Use only non-sparking tools.

P241 Use explosion-proof electrical, ventilating and lighting equipment.

P243 Take action to prevent static discharges.

P233 Keep container tightly closed.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P273 Avoid release to the environment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

Precautionary Statements (Response):

Date / Revised: 14.10.2021 Version: 4.0

Product: N85-021 Thinner 1L

(ID no. 50775814/SDS_GEN_00/EN)

Date of print 09.03.2022

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or physician if you feel unwell.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P370 + P378	In case of fire: Use water spray for extinction.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or physician.
P332 + P313	If skin irritation occurs: Get medical attention.
P303 + P361 + P353	IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P337 + P313	If eye irritation persists: Get medical attention.
P331	Do NOT induce vomiting.

Precautionary Statements (Storage):

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

Other hazards

According to UN GHS criteria

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition/Information on Ingredients

Substances

Not applicable

Mixtures

Chemical nature

organic solvent

<u>Hazardous ingredients (GHS)</u> According to UN GHS criteria

1,2,4-Trimethylbenzene

Date / Revised: 14.10.2021 Version: 4.0

Product: N85-021 Thinner 1L

(ID no. 50775814/SDS_GEN_00/EN)

Date of print 09.03.2022

Content (W/W): >= 2 % - < 2.5 %Asp. Tox. 1 CAS Number: 95-63-6 Flam. Liq. 3

EC-Number: 202-436-9

Acute Tox. 4 (Inhalation - vapour) INDEX-Number: 601-043-00-3 Skin Corr./Irrit. 2

> Aquatic Chronic 2 Eye Dam./Irrit. 2A

STOT SE 3 (irr. to respiratory syst.)

Aquatic Acute 2

H226, H319, H315, H332, H304, H335, H401,

H411

Ethylbenzene

Content (W/W): >= 1 % - < 2 %Asp. Tox. 1 CAS Number: 100-41-4 Flam. Liq. 2

EC-Number: 202-849-4 Acute Tox. 4 (Inhalation - vapour)

INDEX-Number: 601-023-00-4 Acute Tox. 5 (oral)

STOT RE (Auditory organ) 2

Aquatic Acute 2 Aquatic Chronic 3

H225, H332, H303, H304, H373, H412, H401

4-Methylpentan-2-one

Content (W/W): >= 5 % - < 7 %Flam. Liq. 2

CAS Number: 108-10-1 Acute Tox. 4 (Inhalation - vapour)

EC-Number: 203-550-1 Eye Dam./Irrit. 2A

INDEX-Number: 606-004-00-4 STOT SE 3 (irr. to respiratory syst.)

Acute Tox. 5 (oral)

Asp. Tox. 2

H225, H319, H332, H303, H305, H335

EUH066

2-Methoxy-1-methylethyl acetate

Content (W/W): >= 5 % - < 7 %Flam. Liq. 3

CAS Number: 108-65-6 STOT SE 3 (drowsiness and dizziness)

EC-Number: 203-603-9 H226, H336

INDEX-Number: 607-195-00-7

n-Butyl acetate

Content (W/W): >= 50 % - < 75 %Flam. Liq. 3

CAS Number: 123-86-4 STOT SE 3 (drowsiness and dizziness)

EC-Number: 204-658-1 Aquatic Acute 3 INDEX-Number: 607-025-00-1 H226, H336, H402

EUH066

Ethyl 3-ethoxypropionate

Date / Revised: 14.10.2021 Version: 4.0

Product: N85-021 Thinner 1L

(ID no. 50775814/SDS_GEN_00/EN)

Date of print 09.03.2022

Content (W/W): >= 5 % - < 7 % CAS Number: 763-69-9 EC-Number: 212-112-9

Flam. Liq. 3 Acute Tox. 5 (oral) Aquatic Acute 3 Acute Tox. 5 (dermal) H226, H303 + H313, H402

Xylene

Content (W/W): >= 7 % - < 10 % Asp. Tox. 1 CAS Number: 1330-20-7 Flam. Liq. 3

EC-Number: 215-535-7 Acute Tox. 5 (Inhalation - vapour)

INDEX-Number: 601-022-00-9

Acute Tox. 5 (oral)
Skin Corr./Irrit. 2
Eve Dam./Irrit. 2B

STOT SE 3 (irr. to respiratory syst.) STOT RE (Central nervous system, Liver,

Kidney) 2 Aquatic Acute 2 Aquatic Chronic 3

H226, H320, H315, H333, H303, H304, H335,

H373, H412, H401

Solvent naphtha (petroleum), light arom.

Content (W/W): >= 3 % - < 5 % Asp. Tox. 1 CAS Number: 64742-95-6 Flam. Liq. 3 EC-Number: 265-199-0 Skin Corr./Irrit. 2

NDEX-Number: 649-356-00-4 STOT SE 3 (drowsiness and dizziness)

Aquatic Acute 2 Aquatic Chronic 2

H226, H315, H304, H336, H401, H411

EUH066

For the classifications not written out in full in this section the full text can be found in section 16.

4. First-Aid Measures

Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Keep warm, calm and covered up. Immediately remove contaminated clothing. Never give anything by mouth to an unconscious person. In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product. Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.

If inhaled:

Date / Revised: 14.10.2021 Version: 4.0

Product: N85-021 Thinner 1L

(ID no. 50775814/SDS_GEN_00/EN)

Date of print 09.03.2022

Immediate medical attention required. Remove the affected individual into fresh air and keep the person calm. If breathing is irregular or stopped, administer artificial respiration.

On skin contact:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes:

Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

On ingestion:

Summon medical aid without delay. Do not induce vomiting due to aspiration hazard. Rinse mouth immediately with water. Keep at rest.

Most important symptoms and effects, both acute and delayed

Symptoms: Eye irritation, aspiration pneumonia, dazed state, skin irritation, dizziness, Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: If swallowed, in the event of vomiting, risk of product entering the lungs. When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

Indication of any immediate medical attention and special treatment needed

Treatment: Symptomatic treatment (decontamination, vital functions).

Antidote: No known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons: water jet

Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

Advice for fire-fighters

Special protective equipment:

Appropriate breathing apparatus may be required.

Further information:

Date / Revised: 14.10.2021 Version: 4.0

Product: N85-021 Thinner 1L

(ID no. 50775814/SDS_GEN_00/EN)

Date of print 09.03.2022

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

Environmental precautions

Do not allow to enter drains or waterways. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency. Do not discharge into the subsoil/soil.

Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for diposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

7. Handling and Storage

Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eyerinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate)

Date / Revised: 14.10.2021 Version: 4.0

Product: N85-021 Thinner 1L

(ID no. 50775814/SDS_GEN_00/EN)

Date of print 09.03.2022

Further information on storage conditions: Keep container dry. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions.

Storage stability:

Storage temperature: 5,00 - 35,00 °C

Specific end use(s)

Please refer to the technical leaflet for further information.

8. Exposure Controls/Personal Protection

Control parameters

Components with occupational exposure limits

95-63-6: 1,2,4-Trimethylbenzene

100-41-4: Ethylbenzene

108-10-1: 4-Methylpentan-2-one

108-65-6: 2-Methoxy-1-methylethyl acetate

123-86-4: n-Butyl acetate

1330-20-7: Xylene

Exposure controls

Personal protective equipment

Respiratory protection:

Suitable respiratory protection: e.g. half-mask with A1P2 class combination filter When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. Use A1P2 breathing-protection half mask in case of contact with aerosols.

Hand protection:

Further information on penetration time is available from the manufacturer of the glove.

Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.

The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Follow manufacturer's advice on use, storage, maintenance and replacement of gloves.

The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g.

nitrile gloves - material thickness: 0,7 mm

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166), Required when there is a risk of eye contact.

Date / Revised: 14.10.2021 Version: 4.0

Product: N85-021 Thinner 1L

(ID no. 50775814/SDS_GEN_00/EN)

Date of print 09.03.2022

Body protection:

Anti-static protective clothing. Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

General safety and hygiene measures

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Form: liquid Colour: colourless Odour: specific

pH value:

substance/mixture is non-

polar/aprotic

Melting point:

not determined

onset of boiling: 114,00 °C

Flash point: 27 °C (ISO 3679)

Flammability: Flammable liquid and vapour.

Lower explosion limit: 36 g/m3 Ignition temperature: > 200,00 °C

Vapour pressure: 13,00 hPa (calculated)

(20 °C)

(50 °C)

not determined 0,879 g/cm3

Density: (20 °C)

6,0 mm2/s Viscosity, kinematic:

(20 °C)

(40 °C)

not determined not explosive

Explosion hazard: Fire promoting properties: not fire-propagating

Other information

Page: 10/16

Safety data sheet according to UN GHS 4th rev.

Date / Revised: 14.10.2021 Version: 4.0

Product: N85-021 Thinner 1L

(ID no. 50775814/SDS_GEN_00/EN)

Date of print 09.03.2022

Burning rate: The material doesn't meet the criteria (UN Test N.1 (ready

specified in paragraph 33.2.4.4 of UN combustible solids))

manual of tests and criteria.

Self heating ability: It is not a substance capable of

spontaneous heating.

Miscibility with water:

immiscible

Flow time: < 30 s (DIN EN ISO 2431; 3 mm)

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

Vapours may form ignitable mixture with air.

Conditions to avoid

Avoid direct sunlight. Avoid all sources of ignition: heat, sparks, open flame.

Incompatible materials

Substances to avoid:

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

Hazardous decomposition products

:

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

11. Toxicological Information

Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include

Date / Revised: 14.10.2021 Version: 4.0

Product: N85-021 Thinner 1L

(ID no. 50775814/SDS_GEN_00/EN)

Date of print 09.03.2022

headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Based on available data, the classification criteria are not met.

Information on: Ethylbenzene

Experimental/calculated data: LD50 rat (oral): 3.500 mg/kg

Literature data.

Information on: Ethyl 3-ethoxypropionate

Experimental/calculated data:

LD50 rat (oral): 4.309 mg/kg (OECD Guideline 401)

Information on: Xylene

Experimental/calculated data:

LD50 rat (oral): 3.523 mg/kg (similar to OECD guideline 401)

Information on: Ethylbenzene Experimental/calculated data: LD50 rabbit (dermal): 15.354 mg/kg

Literature data.

Irritation

Assessment of irritating effects:

The liquid splashed in the eyes may cause irritation and reversible damage. Eye contact causes irritation. Skin contact causes irritation.

Respiratory/Skin sensitization

Assessment of sensitization:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity

Page: 12/16

Safety data sheet according to UN GHS 4th rev.

Date / Revised: 14.10.2021 Version: 4.0

Product: N85-021 Thinner 1L

(ID no. 50775814/SDS_GEN_00/EN)

Date of print 09.03.2022

Assessment of carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:

Based on available data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness).

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on available data, the classification criteria are not met.

Aspiration hazard

May also damage the lung at swallowing (aspiration hazard).

12. Ecological Information

Toxicity

Assessment of aquatic toxicity:

Harmful to aquatic life. Harmful to aquatic life with long lasting effects. There are no test results available for this product. Do not allow to enter drains or waterways.

Persistence and degradability

Assessment biodegradation and elimination (H2O):

Biological degradability of hazardous substances mentioned in section 3:

Information on: 1,2,4-Trimethylbenzene

Elimination information:

> 20 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EEC, C.4-D) (aerobic, activated sludge, domestic)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Page: 13/16

Safety data sheet according to UN GHS 4th rev.

Date / Revised: 14.10.2021 Version: 4.0

Product: N85-021 Thinner 1L

(ID no. 50775814/SDS_GEN_00/EN)

Date of print 09.03.2022

Information on: Ethylbenzene Elimination information:

70 - 80 % TIC of the ThIC (28 d) (ISO 14593) (aerobic, activated sludge) Readily biodegradable (according to OECD criteria).

Information on: n-Butyl acetate

Elimination information:

80 % BOD of the ThOD (5 d) (OECD 301D; EEC 92/69, C.4-E) (aerobic, municipal sewage treatment plant effluent)

Information on: Ethyl 3-ethoxypropionate

Elimination information:

100 % CO2 formation relative to the theoretical value (28 d) (Directive 84/449/EEC, C.5) (aerobic, activated sludge, domestic, non-adapted) Readily biodegradable.

100 % CO2 formation relative to the theoretical value (18 d) (OECD 301B; ISO 9439; 92/69/EEC, C.4-C) (aerobic)

Information on: Xylene Elimination information:

87,8 % BOD of the ThOD (28 d) (OECD Guideline 301 F) (aerobic, activated sludge, domestic, non-adapted)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: Solvent naphtha (petroleum), light arom.

Elimination information:

77 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EEC, C.4-D) (aerobic, activated sludge, domestic, non-adapted)

96 % CO2 formation relative to the theoretical value (28 d) (ISO 14593) (aerobic, activated sludge, domestic, adapted)

Bioaccumulative potential

Bioaccumulation potential:

No data available.

Mobility in soil

Assessment transport between environmental compartments:

Adsorption in soil: No data available.

13. Disposal Considerations

Waste treatment methods

Observe national and local legal requirements.

Page: 14/16

Safety data sheet according to UN GHS 4th rev.

Date / Revised: 14.10.2021 Version: 4.0

Product: N85-021 Thinner 1L

(ID no. 50775814/SDS_GEN_00/EN)

Date of print 09.03.2022

No disposal via sewage or waste water systems.

Contaminated packaging:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

14. Transport Information

Land transport

ADR

UN number UN1263

UN proper shipping name: PAINT RELATED MATERIAL

Transport hazard class(es): 3
Packing group: III
Environmental hazards: no

Special precautions for Tunnel code: D/E

user:

RID

UN number UN1263

UN proper shipping name: PAINT RELATED MATERIAL

Transport hazard class(es): 3
Packing group: III
Environmental hazards: no

Special precautions for None known

user:

Inland waterway transport

ADN

UN number UN1263

UN proper shipping name: PAINT RELATED MATERIAL

Transport hazard class(es): 3
Packing group: III
Environmental hazards: no

Special precautions for None known

user:

Transport in inland waterway vessel

Not evaluated

Sea transport

Date / Revised: 14.10.2021 Version: 4.0

Product: N85-021 Thinner 1L

(ID no. 50775814/SDS_GEN_00/EN)

Date of print 09.03.2022

IMDG

UN number: UN 1263

UN proper shipping name: PAINT RELATED MATERIAL

Transport hazard class(es): 3
Packing group: III
Environmental hazards: no

Marine pollutant: NO

Special precautions for

r None known

user:

Air transport

IATA/ICAO

UN number: UN 1263

UN proper shipping name: PAINT RELATED MATERIAL

Transport hazard class(es): 3 Packing group: III

Environmental hazards: No Mark as dangerous for the environment is needed

Special precautions for None known

user:

Transport in bulk according to Annex II of MARPOL and the IBC Code

Regulation:
Shipment approved:
Pollution name:
Pollution category:
Ship Type:
Not evaluated
Not evaluated
Not evaluated
Not evaluated
Not evaluated

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable

16. Other Information

For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.

Full text of classifications, hazard symbols and hazard statements, if mentioned in section 2 or 3:

Skin Corr./Irrit. Skin corrosion/irritation

Eye Dam./Irrit. Serious eye damage/eye irritation

Date / Revised: 14.10.2021 Version: 4.0

Product: N85-021 Thinner 1L

(ID no. 50775814/SDS_GEN_00/EN)

Date of print 09.03.2022

Asp. Tox. Aspiration hazard

STOT SE Specific target organ toxicity — single exposure Aquatic Acute Hazardous to the aquatic environment - acute Hazardous to the aquatic environment - chronic

Flam. Liq. Flammable liquids Acute Tox. Acute toxicity

STOT RE Specific target organ toxicity — repeated exposure

H226 Flammable liquid and vapour. H319 Causes serious eye irritation.

H315 Causes skin irritation. H332 Harmful if inhaled.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

H225 Highly flammable liquid and vapour.

H303 May be harmful if swallowed.

H373 May cause damage to organs (Auditory organ) through prolonged or

repeated exposure.

H412 Harmful to aquatic life with long lasting effects.
H305 May be harmful if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H402 Harmful to aquatic life.

H303 + H313 May be harmful if swallowed or in contact with skin

H320 Causes eye irritation. H333 May be harmful if inhaled.

EUH066 Repeated exposure may cause skin dryness or cracking.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.