

# Safety data sheet

Page: 1/13

BASF Safety data sheet according to UN GHS 4th rev. Date / Revised: 16.12.2022 Product: **N95-060 Silicone Cleaner 5L** 

Version: 3.3

(ID no. 50810791/SDS\_GEN\_00/EN)

Date of print 02.06.2023

# 1. Identification

**Product identifier** 

# N95-060 Silicone Cleaner 5L

# Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Thinner

# Details of the supplier of the safety data sheet

<u>Company:</u> BASF France SAS 49, avenue Georges Pompidou 92593 Levallois-Perret Cedex, FRANCE

Telephone: +33 1 4964-5732 E-mail address: securite-produits.france@basf.com

# **Emergency telephone number**

International emergency number: Telephone: +49 180 2273-112

# 2. Hazards Identification

# Classification of the substance or mixture

According to UN GHS criteria

Skin Corr./Irrit. 3 Asp. Tox. 1 STOT SE 3 (Vapours may cause drowsiness and dizziness.) Aquatic Acute 2 Aquatic Chronic 2

Page: 2/13

Version: 3.3

Safety data sheet according to UN GHS 4th rev. Date / Revised: 16.12.2022 Product: **N95-060 Silicone Cleaner 5L** 

(ID no. 50810791/SDS\_GEN\_00/EN) Date of print 02.06.2023

# Flam. Liq. 3

For the classifications not written out in full in this section the full text can be found in section 16.

# Label elements

Globally Harmonized System, UN (GHS)

Pictogram:



Signal Word: Danger

Hazard Statement: H226 H304 H316 H336 H411	Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes mild skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.	
Precautionary Statements (Prevention):		
P280	Wear protective gloves, protective clothing and eye protection or face protection.	
P273	Avoid release to the environment.	
P271	Use only outdoors or in a well-ventilated area.	
P242	Use only non-sparking tools.	
P241	Use explosion-proof electrical, ventilating and lighting equipment.	
P243	Take action to prevent static discharges.	
P233	Keep container tightly closed.	
P210	Keep away from heat, hot surfaces, sparks, open flames and other	
	ignition sources. No smoking.	
P240	Ground and bond container and receiving equipment.	
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.	
Precautionary Statemen	ts (Response):	
P312	Call a POISÓN CENTER or physician if you feel unwell.	
P370 + P378	In case of fire: Use water spray for extinction.	
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or physician.	
P332 + P313	If skin irritation occurs: Get medical attention.	
P303 + P361 + P353	IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower.	
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P331	Do NOT induce vomiting.	
P391	Collect spillage.	
Precautionary Statements (Storage):		
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.	
P403 + P235	Store in a well-ventilated place. Keep cool.	
P405	Store locked up.	

Page: 3/13

Safety data sheet according to UN GHS 4th rev. Date / Revised: 16.12.2022 Product: **N95-060 Silicone Cleaner 5L** 

Version: 3.3

(ID no. 50810791/SDS\_GEN\_00/EN)

Date of print 02.06.2023

Precautionary Statements (Disposal): P501 Dispose of contents and container to hazardous or special waste collection point.

Other hazards

According to UN GHS criteria

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

# 3. Composition/Information on Ingredients

# Substances

Not applicable

### **Mixtures**

Chemical nature

organic solvent

Hazardous ingredients (GHS) According to UN GHS criteria

aliphatic hydrocarbons

Content (W/W): >= 75 % - <= 100 % CAS Number: 64741-69-1 EC-Number: 265-071-4 REACH registration number: 01-2119480158-34 Asp. Tox. 1 Flam. Liq. 3 STOT SE 3 (drowsiness and dizziness) Aquatic Chronic 2 Aquatic Acute 2 H411, H226, H304, H336 EUH066

2-Methoxy-1-methylethyl acetate Content (W/W): >= 3 % - < 5 % CAS Number: 108-65-6 EC-Number: 203-603-9 INDEX-Number: 607-195-00-7

Flam. Liq. 3 STOT SE 3 (drowsiness and dizziness) H226, H336

Ethyl 3-ethoxypropionate Content (W/W): >= 3 % - < 5 % CAS Number: 763-69-9 EC-Number: 212-112-9

Flam. Liq. 3 Acute Tox. 5 (oral) Aquatic Acute 3 Acute Tox. 5 (dermal) H226, H303 + H313, H402

Page: 4/13

Safety data sheet according to UN GHS 4th rev. Date / Revised: 16.12.2022 Product: **N95-060 Silicone Cleaner 5L** 

Version: 3.3

(ID no. 50810791/SDS\_GEN\_00/EN)

Date of print 02.06.2023

	Date of print officer
Content (W/W): >= 1 % - < 2 %	Asp. Tox. 1
CAS Number: 95-63-6	Flam. Liq. 3
EC-Number: 202-436-9	Acute Tox. 4 (Inhalation - vapour)
INDEX-Number: 601-043-00-3	Skin Corr./Irrit. 2
	Aquatic Chronic 2
	Eye Dam./Irrit. 2A
	STOT SE 3 (irr. to respiratory syst.)
	Aquatic Acute 2
	H226, H319, H315, H332, H304, H335, H401,
	H411

For the classifications not written out in full in this section the full text can be found in section 16.

# 4. First-Aid Measures

### **Description of first aid measures**

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Keep warm, calm and covered up. Immediately remove contaminated clothing. Never give anything by mouth to an unconscious person. In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product. Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.

### If inhaled:

Immediate medical attention required. Remove the affected individual into fresh air and keep the person calm. If breathing is irregular or stopped, administer artificial respiration.

### On skin contact:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

### On contact with eyes:

If symptoms persist, seek medical advice. Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution.

### On ingestion:

Summon medical aid without delay. Do not induce vomiting due to aspiration hazard. Rinse mouth immediately with water. Keep at rest.

# Most important symptoms and effects, both acute and delayed

Symptoms: aspiration pneumonia, dazed state, skin irritation, dizziness, Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: If swallowed, in the event of vomiting, risk of product entering the lungs. When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

# Indication of any immediate medical attention and special treatment needed

Treatment: Symptomatic treatment (decontamination, vital functions). Antidote: No known specific antidote.

Page: 5/13

Safety data sheet according to UN GHS 4th rev. Date / Revised: 16.12.2022 Product: **N95-060 Silicone Cleaner 5L** 

Version: 3.3

(ID no. 50810791/SDS\_GEN\_00/EN) Date of print 02.06.2023

# 5. Fire-Fighting Measures

### **Extinguishing media**

Suitable extinguishing media: carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons: water jet

### Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

# Advice for fire-fighters

Special protective equipment: Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

# 6. Accidental Release Measures

### Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

### **Environmental precautions**

Do not allow to enter drains or waterways. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency. Do not discharge into the subsoil/soil.

### Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for diposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

# 7. Handling and Storage

# Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the

Page: 6/13

Safety data sheet according to UN GHS 4th rev. Date / Revised: 16.12.2022 Product: **N95-060 Silicone Cleaner 5L** 

Version: 3.3

(ID no. 50810791/SDS\_GEN\_00/EN)

Date of print 02.06.2023

particulates and solvent vapour concentration has fallen below the exposure limits. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eyerinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

### Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: glass, Stainless steel 1.4301 (V2), Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container dry. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing.

Storage stability: Storage temperature: 5,00 - 40,00 °C

# Specific end use(s)

Please refer to the technical leaflet for further information.

# 8. Exposure Controls/Personal Protection

## **Control parameters**

Components with occupational exposure limits

95-63-6: 1,2,4-Trimethylbenzene 108-65-6: 2-Methoxy-1-methylethyl acetate

### **Exposure controls**

Personal protective equipment

Respiratory protection:

Suitable respiratory protection: e.g. half-mask with A1P2 class combination filter When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. Use A1P2 breathing-protection half mask in case of contact with aerosols.

Hand protection:

Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.

The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Follow manufacturer's advice on use, storage, maintenance and replacement of gloves.

Page: 7/13

Safety data sheet according to UN GHS 4th rev. Date / Revised: 16.12.2022 Product: **N95-060 Silicone Cleaner 5L** 

Version: 3.3

(ID no. 50810791/SDS\_GEN\_00/EN)

Date of print 02.06.2023

The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g.

nitrile gloves - material thickness: 0,7 mm

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6,

corresponding > 480 minutes of permeation time according to EN ISO 374-1):

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166), Required when there is a risk of eye contact.

Body protection:

Anti-static protective clothing, Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

General safety and hygiene measures

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

# 9. Physical and Chemical Properties

# Information on basic physical and chemical properties

Form: Colour: Odour: pH value:	liquid colourless of petroleum distillate (e.g. gasoline, k	erosene)
	substance/mixture is non- polar/aprotic	
Melting point:		
	not determined	
onset of boiling:	135 °C	(calculated)
Flash point:	24 °C	(ISO 3679)
Flammability:	Flammable liquid and vapour.	
Lower explosion limit:	36 g/m3	
Ignition temperature: Vapour pressure:	> 200,00 °C	
	(20 °C)	
	not determined	
	(50 °C)	
	not determined	
Density:	0,779 g/cm3	
-	(20 °C)	

Page: 8/13

Safety data sheet according to UN GHS 4th rev. Date / Revised: 16.12.2022 Product: **N95-060 Silicone Cleaner 5L** 

Version: 3.3

(ID no. 50810791/SDS\_GEN\_00/EN)

Date of print 02.06.2023

Relative vapour density (	air): Heavier than air.	
Partitioning coefficient n-octanol/water (log Kow):		
	not applicable for mixtures	
Self ignition:	Unspecified	
Thermal decomposition: Viscosity, kinematic:	No decomposition if stored and handle 6,0 mm2/s (20 °C)	d as prescribed/indicated.
	(40 °C)	
	not determined	
Explosion hazard: Fire promoting properties	not explosive not fire-propagating	
Other information		
Burning rate:	The material doesn't meet the criteria specified in paragraph 33.2.4.4 of UN	
Self heating ability:	manual of tests and criteria. It is not a material capable of spontaneous heating	
Miscibility with water:		
Flow time:	immiscible < 30 s	(DIN EN ISO 2421: 2 mm)
	< 30.5	(DIN EN ISO 2431; 3 mm)

# 10. Stability and Reactivity

# Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

# **Chemical stability**

The product is stable if stored and handled as prescribed/indicated.

# Possibility of hazardous reactions

Vapours may form ignitable mixture with air.

# **Conditions to avoid**

:

Avoid direct sunlight. Avoid all sources of ignition: heat, sparks, open flame. Avoid freezing.

# Incompatible materials

Substances to avoid: Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

# Hazardous decomposition products

Page: 9/13

Safety data sheet according to UN GHS 4th rev. Date / Revised: 16.12.2022 Product: **N95-060 Silicone Cleaner 5L** 

Version: 3.3

(ID no. 50810791/SDS\_GEN\_00/EN)

Date of print 02.06.2023

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

# **11. Toxicological Information**

# Information on toxicological effects

### Acute toxicity

### Assessment of acute toxicity:

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Based on available data, the classification criteria are not met.

### Irritation

Assessment of irritating effects: The liquid splashed in the eyes may cause irritation and reversible damage. Skin contact causes slight irritation.

### Respiratory/Skin sensitization

Assessment of sensitization: Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

Assessment of mutagenicity: Based on available data, the classification criteria are not met.

### Carcinogenicity

Assessment of carcinogenicity: Based on available data, the classification criteria are not met.

### Reproductive toxicity

Assessment of reproduction toxicity: Based on available data, the classification criteria are not met.

### Developmental toxicity

Assessment of teratogenicity: Based on available data, the classification criteria are not met.

Page: 10/13

Safety data sheet according to UN GHS 4th rev. Date / Revised: 16.12.2022 Product: **N95-060 Silicone Cleaner 5L** 

Version: 3.3

(ID no. 50810791/SDS\_GEN\_00/EN) Date of print 02.06.2023

Specific target organ toxicity (single exposure)

Assessment of STOT single: Possible narcotic effects (drowsiness or dizziness).

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity: Based on available data, the classification criteria are not met.

Aspiration hazard

May also damage the lung at swallowing (aspiration hazard).

# **12. Ecological Information**

# Toxicity

Assessment of aquatic toxicity:

Toxic to aquatic life. Toxic to aquatic life with long lasting effects. There are no test results available for this product. Do not allow to enter drains or waterways.

# Persistence and degradability

Assessment biodegradation and elimination (H2O): Biological degradability of hazardous substances mentioned in section 3:

Information on: 1,2,4-Trimethylbenzene Elimination information: > 20 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EEC, C.4-D) (aerobic, activated sludge, domestic) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: Ethyl 3-ethoxypropionate Elimination information: 100 % CO2 formation relative to the theoretical value (28 d) (Directive 84/449/EEC, C.5) (aerobic, activated sludge, domestic, non-adapted) Readily biodegradable.

100 % CO2 formation relative to the theoretical value (18 d) (OECD 301B; ISO 9439; 92/69/EEC, C.4-C) (aerobic)

# **Bioaccumulative potential**

Bioaccumulation potential: No data available.

# Mobility in soil

Assessment transport between environmental compartments: Adsorption in soil: No data available.

Page: 11/13

Safety data sheet according to UN GHS 4th rev. Date / Revised: 16.12.2022 Product: **N95-060 Silicone Cleaner 5L** 

Version: 3.3

(ID no. 50810791/SDS\_GEN\_00/EN) Date of print 02.06.2023

# **13. Disposal Considerations**

### Waste treatment methods

Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.

Contaminated packaging: Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

# 14. Transport Information

### Land transport

# ADR

UN number or ID number: UN proper shipping name:	UN1993 FLAMMABLE LIQUID, N.O.S. (contains NAPHTHA (PETROLEUM), LIGHT HYDROCRACKED)
Transport hazard class(es): Packing group: Environmental hazards: Special precautions for user:	3, EHSM III yes Tunnel code: D/E
RID	
UN number or ID number: UN proper shipping name:	UN1993 FLAMMABLE LIQUID, N.O.S. (contains NAPHTHA (PETROLEUM), LIGHT HYDROCRACKED)
Transport hazard class(es): Packing group: Environmental hazards: Special precautions for user:	3, EHSM III yes None known
<u>Inland waterway transport</u> ADN	
UN number or ID number: UN proper shipping name:	UN1993 FLAMMABLE LIQUID, N.O.S. (contains NAPHTHA (PETROLEUM), LIGHT HYDROCRACKED)
Transport hazard class(es): Packing group: Environmental hazards: Special precautions for	3, EHSM III yes None known

Page: 12/13

Safety data sheet according to UN GHS 4th rev. Date / Revised: 16.12.2022 Product: **N95-060 Silicone Cleaner 5L** 

Version: 3.3

(ID no. 50810791/SDS\_GEN\_00/EN) Date of print 02.06.2023

user:

<u>Transport in inland waterway vessel</u> Not evaluated

### Sea transport

IMDG

UN number or ID number: UN proper shipping name:	UN 1993 FLAMMABLE LIQUID, N.O.S. (contains NAPHTHA (PETROLEUM), LIGHT HYDROCRACKED)
Transport hazard class(es): Packing group: Environmental hazards:	3, EHSM III yes Marine pollutant: YES
Special precautions for user:	EmS: F-E; <u>S-E</u>

### Air transport

IATA/ICAO

UN number or ID number: UN proper shipping name:	UN 1993 FLAMMABLE LIQUID, N.O.S. (contains NAPHTHA (PETROLEUM), LIGHT HYDROCRACKED)
Transport hazard class(es): Packing group: Environmental hazards: Special precautions for user:	3 III No Mark as dangerous for the environment is needed None known

# Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

# **15. Regulatory Information**

Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable

# 16. Other Information

For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.

Page: 13/13

Safety data sheet according to UN GHS 4th rev. Date / Revised: 16.12.2022 Product: **N95-060 Silicone Cleaner 5L** 

Version: 3.3

(ID no. 50810791/SDS\_GEN\_00/EN)

Date of print 02.06.2023

Full text of classifications, hazard symbols and hazard statements, if mentioned in section 2 or 3:		
Skin Corr./Irrit.	Skin corrosion/irritation	
Asp. Tox.	Aspiration hazard	
STOT SE	Specific target organ toxicity — single exposure	
Aquatic Acute	Hazardous to the aquatic environment - acute	
Aquatic Chronic	Hazardous to the aquatic environment - chronic	
Flam. Liq.	Flammable liquids	
Acute Tox.	Acute toxicity	
Eye Dam./Irrit.	Serious eye damage/eye irritation	
H411	Toxic to aquatic life with long lasting effects.	
H226	Flammable liquid and vapour.	
H304	May be fatal if swallowed and enters airways.	
H336	May cause drowsiness or dizziness.	
H303 + H313	May be harmful if swallowed or in contact with skin	
H402	Harmful to aquatic life.	
H319	Causes serious eye irritation.	
H315	Causes skin irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H401	Toxic to aquatic life.	
EUH066	Repeated exposure may cause skin dryness or cracking.	

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.